

## **EC Declaration of Conformity**

for mortar

### **KAMENOL**

Medium-bed cement-based polymer enriched mortar for laying of stone, stone tiles, clinker, terracotta tiles and mosaic into 5 to 15 mm layers. For interior and exterior applications.

Manufacturer and the authorized representative established within the European Economic Area:

KEMA Puconci d.o.o.  
Puconci 109,  
9201 Puconci,  
SLOVENIA

herewith declare that the product **KAMENOL**  
in accordance with Initial Type Test:

**No. 03/07**

Issued by:

Name and address notified certification body: **Razvojni laboratorij**  
**KEMA Puconci d.o.o.**  
**Puconci 109, 9201 Puconci**

and that the standard referenced below have been applied:

**EN 998-2:2004**

and complies the requirements for industrial prepared mortal, which conformity is examined by system of conformity 4 (table ZA 2, standard EN 998-2:2004) and complies the requirements for setting up the CE mark from table ZA 4, standard EN 998-2:2004.

For the evaluation of conformity examinations from table ZA 1, standard EN 998-2:2004 have been made.

Product is submitted to factory production control according to standard EN 998-2:2004.

Puconci, 20.03. 2009

Mark

Development and Quality  
Manager:  
Stanko Polajner



**KEMA Puconci d.o.o.**



KEMA Puconci d.o.o.,

Puconci 109, 9201 Puconci, SLOVENIA

07

**EN 998-2**

**KAMENOL Mortar for stone laying**

The factory prepared mortar for stone laying, for interior and exterior applications on the construction elements, according to the constructional requirements.

|  |  |
|--|--|
| <b>Composition:</b>                    | Cement 40 %<br>Mineral aggregate 59 %<br>Organic binders 1 % |
| <b>Flexural strength</b>               | 6,2 N/mm <sup>2</sup> (28 days on dry)                       |
| <b>Compressive strength</b>            | 26,1 N/mm <sup>2</sup> (28 days on dry)                      |
| <b>Adhesive Bond on concrete plate</b> | 0,95 N/mm <sup>2</sup> (28 days on dry)                      |
| <b>Density of hardened mortar</b>      | 1822 kg/m <sup>3</sup>                                       |